


STOREBRO 31 PC























STOREBRO 31 PC personnel carrier

Developed by Storebro Bruks AB in close cooperation with the Royal Swedish Navy for ship to shore communications and for crew transports in their naval bases. Suitable for all kinds of personnel transports including taxi service and with minor additions also for ambulance transports taking up to four stretchers.

SPECIFICATION

Hull:
Hand laid glass reinforced plastic in accordance with "Det Norske Veritas" standards.

Superstructure:

Hand laid glass reinforced plastic in single and sand-

	approx.	
Length	9.30 m	30'6"
Beam	3.30 m	10'10"
Draft	1.00 m	3'3"
Height above water lin	e	
(excluding mast)	2.25 m	7'5"
Height in cradle	3.10 m	10'2"
Number of seats	Helmsman, navigator and 21 passengers	
Freeboard:	approx.	
forward	1.4 m	4'7
aft	1.2 m	3'11"
Weight	5,5 tons	5,5 tons
Fuel capacity	2x325 l	2x72 imp.gall.

Engine alternatives:

ngine alternatives:
Single or twin installations of Volvo Penta diesels MD
40 A 79 hp/58 kW (light commercial use 72 hp/53 kW)
TMD 40 A 117 hp/86 kW (light ceommercial use 91
hp/67 kW) TAMD 40 A 141 hp/104 kW (light commercial use 110 hp/81 kW) TAMD 60 B 221 hp/163
kW (light commercial use 184 hp/135 kW)

Reversing gear:
on; MD 40 A, TMD 40 A and TAMD 40 A; Borg
Warner hydraulic gear.
on; TAMD 60 B; Twin Disc hydraulic gear.

Batteries:

Electrics: 12 Volts Batteries 3x160 Ah

STANDARD EQUIPMENT

Deck Fittings:
3 pairs of stainless bollards - Stem fitting with stem-3 pairs of stainless bollards — Stem litting with stem-head roller — Safety glass in all windows — Three windscreen wipers — Navigation lights to internatio-nal standards — Boat hook, flag pole and mast — Stainless steel transom ladder — Four inflatable life rafts — Heavy duty rubbing strakes — 4 Skylights — Fore deck hatch — Stainless steel railings — Ventilators.

Main cabin:

lain cabin:

12 passenger seats - Sprung seats for helmsman and
navigator - Chart table - Lockers - Ash trays Cabin lights - Leading lights on floorboards and stairis - Forward boarding hatch with stairs - Fire extinguisher - Complete engine instrumentation Storage for lifebelts under each seat - Two skylights
- Morse engine controls - Teleflex/Morse steering Electric central - Fuel gauges - Manual bilge pump
- Electric bilge pump Electric central — Fue — Electric bilge pump.

Self bailing - Boarding ladders - Leading lights for boarding ladders - Manual bilge pump.

After deck:

nter deck:
Seating accomodations for 9 passengers — Fire extinguisher — Storage for life belts — Manual bilge pump — Electric bilge pump — Emergency hatch to after deck — Ample lighting — Ash trays.

ngme room.
Flexible engine mountings – Drip trays integrated in
the hull under the engines – Fuel filters – Sea water
filters – Electric bilge pump – Manual bilge pump –
Alternator(s) – Fire extinguisher for engine room, Alternator(s) - Fire extinguisher Halon - Stainless steel fuel tanks.

Miscellaneous:

hiscellaneous:
Generous lighting throughout — 12 V outlet sockets
Batteries — Emergency tiller — 4 Life rafts for 6
persons each — Ventilators — 4 Lifting eyes — Search
light — Compass — Sumlog — 2 Skylights — 2 Lockers
— Electro hydraulic trimtabs.

The construction is approved by "Det Norske Veritas" whose certificate is issued with each boat delivered. Some additional accessories are shown in the illustrations.

The manufacturer reserve the right to make alterations without notice.

Design: J.H. Lindblom in cooperation with the Royal Swedish Navy.

Builders: Storebro Bruks AB, Sweden.

S-590 83 STOREBRO, SWEDEN - TEL. 0492/301 60 - CABLE "STOREBROBRUK" VIMMERBY - TELEX 3943 STB